



Revision Date: 08/13/2009

SECTION I - PRODUCT AND COMPANY IDENTIFICATION

Identity: STANDARD BRICK

Trade Names: Select, Hen's Egg, Arctic White, Buckwheat, Golden Buff, Old Gold, Copperstone, Bronzestone, Canyon Rose, Canyonstone, Park Rose, Mountain Red, Monterey, Redwood Spice, Desert Dawn, Mission San Jose, Manhattan Rose, Chippewa, Baja Brown, Ironstone, Desert Sand, Sunset, Autumn Red, Almond, Ochre Buff

Manufacturer's Name: Interstate Brick
9780 South 5200 West
Utah, UT 84088-5689

Emergency Telephone Number: (801) 280-5200 MSDS Information Tel. No.: (916)339 - 8127

SECTION II - PRODUCT AND COMPONENT DATA

Table with 5 columns: Composition, CAS Number, % By Weight, ACGIH TLV, OSHA PEL. Rows include Clay/Shale (Aluminum Silicates) and Barium Carbonate.

EXPOSURE LIMITS:

Table with 4 columns: Composition, CAS Number, ACGIH TLV, OSHA PEL. Rows include Crystalline Silica (Quartz) and Barium.

OSHA PEL for crystalline silica in the form of quartz is = 10 mg/m³ ÷ (% SiO₂) , and 50% of this value for cristobalite and tridymite.

SECTION III - HEALTH HAZARD and FIRST AID INFORMATION

CHRONIC HAZARDS:

Primary Route of Exposure: Inhalation

Exposure Limits: (Acceptable exposure levels for this product must be defined in the workplace due to the combination of silica and other constituents and condition of use.) Unless specified otherwise, limits are expressed as eight-hour Time-weighted averages (TWA). Limits for cristobalite and tridymite (other forms of crystalline silica) are equal to one-half of the limits for quartz.

Particulates or Dust: TLV - 10mg/m³ (total particulate) or 3mg/m³ (respirable particulate), not otherwise classified; OSHA PEL.= 15 mg/m³ (total particulate, not otherwise regulated). OSHA PEL = 5 mg/m³ (respirable particulate, not otherwise regulated).

Respirable Crystalline Silica (quartz): TLV =  $0.1 \text{ mg/m}^3$ ; OSHA PEL =  $10 \text{ mg/m}^3 \div (\% \text{SiO}_2 + 2)$ ; OSHA Proposed PEL  $0.1 \text{ mg/m}^3$

Respirable Dust containing silica: OSHA PEL =  $10 \text{ mg/m}^3 \div (\% \text{SiO}_2 + 2)$

Total Dust containing silica: OSHA PEL =  $30 \text{ mg/m}^3 \div (\% \text{SiO}_2 + 2)$

ACGIH and OSHA have determined that adverse effects are not likely to occur in the workplace provided exposure levels do not exceed the appropriate TLVs/PELs. However, because of the wide variation in individual susceptibility, lower exposure limits may be appropriate for some individuals, including persons with pre-existing medical conditions such as those described below.

**Abbreviations:** TLV = threshold limit value of the American Conference of Governmental Industrial Hygienists (ACGIH); OSHA PEL = permissible exposure limit of the Occupational Safety and Health Administration (OSHA);  $\text{mg/m}^3$  = milligrams of substance per cubic meter of air.

### **SUBCHRONIC AND CHRONIC HEALTH EFFECTS:**

Pulmonary Diseases: Excessive exposure to particulates (dust) over an extended period of time may result in the development of silicosis and other pulmonary diseases.

Carcinogenicity: IARC has classified respirable crystalline silica (quartz) a known carcinogen in humans.

**California Proposition 65 Warning:** Dry cutting, sanding or grinding of clay brick products will expose you to respirable crystalline silica which is "known in the State of California to cause cancer and to other substances which are known to the State of California to cause cancer, birth defects and other reproductive harm."

See also: American Society for testing and Materials (ASTM) Standard practice E1132-86, "Standard Practice for Health Requirements Relating to Occupational Exposure to Quartz Dust."

Medical Conditions Aggravated by Exposure: Excessive dust exposure may aggravate any existing respiratory disorders or diseases. Possible complications of allergies resulting in irritation to skin, eyes and respiratory passage may occur from excessive exposure to dusts.

### **ACUTE HAZARDS:**

Eye Contact: Direct contact with dust may cause irritation by mechanical abrasion.

Skin Contact: Direct contact may cause irritation by mechanical abrasion.

Skin Absorption: Not expected to be a significant exposure route.

Ingestion: Expected to be practically non-toxic. Ingestion of large amounts may cause gastrointestinal irritation and blockage.

Inhalation: Dusts may irritate the nose, throat, and respiratory tract by mechanical abrasion. Coughing, sneezing, and shortness of breath may occur following exposures in excess of appropriate exposure limits. Use of natural sand and gravel for construction purposes is not believed to cause additional acute toxic effects. However, repeated overexposure to very high levels of respirable crystalline silica (quartz, cristobalite, tridymite) for periods as short as six months have caused acute silicosis. Acute silicosis is a rapidly progressive, incurable lung disease that is typically fatal. Symptoms include (but are not limited to); shortness of breath, cough, fever, weight loss, and chest pain.

### **FIRST AID:**

**Eyes:** Immediately flush eye(s) with plenty of clean water for at least 15 minutes, while holding the eyelid(s) open. Occasionally lift the eyelid(s) to ensure thorough rinsing. Beyond flushing, do not attempt to remove material from the eye(s). Contact a physician if irritation persists or later develops.

**Skin:** Wash with soap and water. Contact a physician if irritation persists or later develops.

**Ingestion:** If person is conscious, give large quantity of water and induce vomiting; however, never attempt to make an unconscious person drink or vomit. Get immediate medical attention.

**Inhalation:** Remove to fresh air. Dust in throat and nasal passages should clear spontaneously. Contact a physician if irritation persists or later develops.

---

### **SECTION IV - PHYSICAL/CHEMICAL CHARACTERISTICS**

---

Boiling Point:	NA	Specific Gravity (H <sub>2</sub> O = 1):	2.6
Vapor Pressure (mm Hg):	NA	Melting Point:	NA
Vapor Density (Air = 1):	NA	Evaporation Rate:	
Solubility in Water:	0	(Butyl Acetate = 1)	NA
Appearance and Odor:	Vitrified solid, essentially odorless, wide range of colors		

---

### **SECTION V - FIRE AND EXPLOSION HAZARD DATA**

---

Flash Point (Method Used): NA	Flammable Limits: NA	LEL: NA	UEL: NA
Extinguishing Media: NA	Special Fire Fighting Procedures: None		
Unusual Fire and Explosion Hazards: None			

---

### **SECTION VI - REACTIVITY DATA**

---

Stability:	Unstable:	Stable: <b>X</b>	Conditions to Avoid: None
Incompatibility (Materials to Avoid):		None known	
Hazardous Decomposition or Byproducts:		None known	
Hazardous Polymerization:	May Occur:	Will Not Occur: <b>X</b>	Conditions to Avoid: None

---

### **SECTION VII - PERSONAL PROTECTION AND CONTROL MEASURES**

---

**RESPIRATORY PROTECTION:** To minimize exposure to dust and/or crystalline silica, cutting or grinding clay brick and other clay products should be conducted with a wet saw/grinder and with sufficient ventilation. When such controls are not feasible, NIOSH/MSHA approved respirators must be worn in accordance with a respiratory protection program which meets OSHA requirements as set forth at 29 CFR 1910.134 and ANSI Z88.2-1080 "Practices for Respiratory Protection."

**SKIN PROTECTION:** Use gloves and/or protective clothing if abrasion or allergic reactions are experienced.

**EYE PROTECTION:** Use safety glasses with side shields. Face shields should also be used when dry sawing clay brick. Dust goggles should be worn when excessively (visible) dusty conditions are present or are anticipated.

**LOCAL EXHAUST:** When dry sawing or grinding clay brick, use sufficient local exhaust to reduce the level of respirable dust to the applicable standards set forth in Section III. See ACGIH "Industrial Ventilation, A Manual of Recommended Practice," latest edition.

**SAFETY MEASURES:** Wear hard hats and/or steel-toed safety shoes if brick may fall from an elevation or be dropped during handling.

**WORK/HYGIENIC PRACTICES:** Avoid creating and breathing dust.

**OTHER CONTROL MEASURES:** Respirable dust and quartz levels should be monitored regularly. Dust and quartz levels in excess of appropriate exposure limits should be reduced by feasible engineering controls, including (but not limited to) wet sanding, wet suppression, ventilation, and process enclosures. Respirators must be worn when such controls are not feasible or do not completely control dust generation.

---

## **SECTION VIII - HANDLING AND STORAGE INFORMATION**

---

**STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:** Use adequate ventilation, dustless vacuum or cleanup systems for handling, storage, and clean-up so that airborne dust does not exceed the PEL. Practice good housekeeping. Do not permit dust to collect on walls, floors, sills, ledges, machinery, or equipment. Maintain, clean, and fit test respirators in accordance with OSHA standards. Maintain and test ventilation and dust collection equipment. Wash or vacuum clothing which becomes dusty. See also control measures in Section VII.

**WASTE DISPOSAL METHOD:** This material is classed as a non-hazardous solid waste for disposal.

**PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING:** None for normal handling and storage of intact bricks. This product is not intended or designed for use as an abrasive blasting medium or for foundry applications and should not be used for those purposes. Do not store near food and beverages or smoking materials.

**OTHER REGULATIONS:** Community Right-To-Know = this product is not subject to the reporting requirements of the Emergency Planning and Community Right-To-Know Act of 1987(EPCRA) [ 40 CFR 370 and 372].

**TRANSPORTATION:** DOT Hazard Classification: Not Regulated  
UN/NA Code: None Placard  
Required: None. Labeling  
Requirement: None.

---

## **SECTION IX - OTHER INFORMATION**

---

**The information and recommendations contained herein are based upon the data believed to be correct. However, no guarantee or warranty of any kind, express or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful health effects, which may be caused by exposure to airborne dust particles created by dry sawing of grinding of our products. Customers/users of clay brick products must comply with all applicable health and safety laws, regulations, and orders.**

MSDS STATUS: Revision 3  
PREPARER: Sunup Mathew, SE LEED  
Title: Technical Director  
Telephone No: ( 801) 280-5228